



Financial products Markup Language

FpML 4.0 - Risk Definitions Component Definitions

Version: 4.2

This Version:

<http://www.fpml.org/spec/2006/tr-fpml-4-2-2006-05-08>

Latest Version:

<http://www.fpml.org/spec/2006/tr-fpml-4-2-2006-05-08>

Previous Version:

<http://www.fpml.org/spec/2006/lcwg-fpml-4-2-2006-03-15/>

Errata For This Version:

<http://www.fpml.org/spec/errata/tr-fpml-4-2-2006-05-08-errata.html>

Document built

Copyright (c) 1999 - 2006 by INTERNATIONAL SWAPS AND DERIVATIVES ASSOCIATION, INC.

Financial Products Markup Language is subject to the FpML Public License.

A copy of this license is available at <http://www.fpml.org/documents/license.html>

The FpML specifications provided are without warranty of any kind, either expressed or implied, including, without limitation, warranties that FpML, or the FpML specifications are free of defects, merchantable, fit for a particular purpose or non-infringing. The entire risk as to the quality and performance of the specifications is with you. Should any of the FpML specifications prove defective in any respect, you assume the cost of any necessary servicing or repair. Under no circumstances and under no legal theory, whether tort (including negligence), contract, or otherwise, shall ISDA, any of its members, or any distributor of documents or software containing any of the FpML specifications, or any supplier of any of such parties, be liable to you or any other person for any indirect, special, incidental, or consequential damages of any character including, without limitation, damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses, even if such party shall have been informed of the possibility of such damages.

Table Of Contents

| | | |
|-------|--------------------------------|----|
| 1 | Global Complex Types | 6 |
| 1.1 | DenominatorTerm | 7 |
| 1.1.1 | Description: | 7 |
| 1.1.2 | Contents: | 7 |
| 1.1.3 | Used by: | 7 |
| 1.1.4 | Derived Types: | 7 |
| 1.1.5 | Figure: | 7 |
| 1.1.6 | Schema Fragment: | 7 |
| 1.2 | DerivativeCalculationMethod | 8 |
| 1.2.1 | Description: | 8 |
| 1.2.2 | Contents: | 8 |
| 1.2.3 | Used by: | 8 |
| 1.2.4 | Derived Types: | 8 |
| 1.2.5 | Figure: | 8 |
| 1.2.6 | Schema Fragment: | 8 |
| 1.3 | DerivativeCalculationProcedure | 9 |
| 1.3.1 | Description: | 9 |
| 1.3.2 | Contents: | 9 |
| 1.3.3 | Used by: | 9 |
| 1.3.4 | Derived Types: | 9 |
| 1.3.5 | Figure: | 9 |
| 1.3.6 | Schema Fragment: | 9 |
| 1.4 | DerivativeFormula | 10 |
| 1.4.1 | Description: | 10 |
| 1.4.2 | Contents: | 10 |
| 1.4.3 | Used by: | 10 |
| 1.4.4 | Derived Types: | 10 |
| 1.4.5 | Figure: | 10 |
| 1.4.6 | Schema Fragment: | 10 |
| 1.5 | FormulaTerm | 11 |
| 1.5.1 | Description: | 11 |
| 1.5.2 | Contents: | 11 |
| 1.5.3 | Used by: | 11 |
| 1.5.4 | Derived Types: | 11 |
| 1.5.5 | Figure: | 11 |
| 1.5.6 | Schema Fragment: | 11 |
| 1.6 | PerturbationType | 12 |
| 1.6.1 | Description: | 12 |
| 1.6.2 | Contents: | 12 |
| 1.6.3 | Used by: | 12 |
| 1.6.4 | Derived Types: | 12 |
| 1.6.5 | Figure: | 12 |
| 1.6.6 | Schema Fragment: | 12 |
| 1.7 | PricingParameterDerivative | 13 |
| 1.7.1 | Description: | 13 |
| 1.7.2 | Contents: | 13 |
| 1.7.3 | Used by: | 13 |
| 1.7.4 | Derived Types: | 13 |
| 1.7.5 | Figure: | 13 |
| 1.7.6 | Schema Fragment: | 13 |
| 1.8 | PricingParameterShift | 15 |
| 1.8.1 | Description: | 15 |
| 1.8.2 | Contents: | 15 |
| 1.8.3 | Used by: | 15 |
| 1.8.4 | Derived Types: | 15 |
| 1.8.5 | Figure: | 15 |
| 1.8.6 | Schema Fragment: | 15 |
| 1.9 | SensitivityDefinition | 17 |
| 1.9.1 | Description: | 17 |
| 1.9.2 | Contents: | 17 |

| | | |
|--------|---------------------------|----|
| 1.9.3 | Used by: | 17 |
| 1.9.4 | Derived Types: | 17 |
| 1.9.5 | Figure: | 17 |
| 1.9.6 | Schema Fragment: | 17 |
| 1.10 | SensitivitySetDefinition | 19 |
| 1.10.1 | Description: | 19 |
| 1.10.2 | Contents: | 19 |
| 1.10.3 | Used by: | 19 |
| 1.10.4 | Derived Types: | 19 |
| 1.10.5 | Figure: | 19 |
| 1.10.6 | Schema Fragment: | 20 |
| 1.11 | WeightedPartialDerivative | 22 |
| 1.11.1 | Description: | 22 |
| 1.11.2 | Contents: | 22 |
| 1.11.3 | Used by: | 22 |
| 1.11.4 | Derived Types: | 22 |
| 1.11.5 | Figure: | 22 |
| 1.11.6 | Schema Fragment: | 22 |
| 2 | Schema listing | 23 |

1 Global Complex Types

1.1 DenominatorTerm

1.1.1 Description:

The type defining a denominator term of the formula. Its value is (sum of weighted partials) ^ power.

1.1.2 Contents:

weightedPartial (exactly one occurrence; of the type WeightedPartialDerivative) A partial derivative multiplied by a weighting factor.


power (exactly one occurrence; of the type xsd:integer) The power to which this term is raised.

1.1.3 Used by:

- Complex type: DerivativeFormula

1.1.4 Derived Types:

1.1.5 Figure:



1.1.6 Schema Fragment:

```
<xsd:complexType name="DenominatorTerm">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">
      The type defining a denominator term of the formula. Its value is
      (sum of weighted partials) ^ power.
    </xsd:documentation>
  </xsd:annotation>
  <xsd:sequence>
    <xsd:element name="weightedPartial" type="WeightedPartialDerivative">
      <xsd:annotation>
        <xsd:documentation xml:lang="en">
          A partial derivative multiplied by a weighting factor.
        </xsd:documentation>
      </xsd:annotation>
    </xsd:element>
    <xsd:element name="power" type="xsd:integer">
      <xsd:annotation>
        <xsd:documentation xml:lang="en">
          The power to which this term is raised.
        </xsd:documentation>
      </xsd:annotation>
    </xsd:element>
  </xsd:sequence>
</xsd:complexType>
```

1.2 DerivativeCalculationMethod

1.2.1 Description:

The method by which a derivative is computed.

1.2.2 Contents:


Inherited element(s): (This definition inherits the content defined by the type xsd:normalizedString)

1.2.3 Used by:

- Complex type: DerivativeCalculationProcedure

1.2.4 Derived Types:

1.2.5 Figure:



1.2.6 Schema Fragment:

```
<xsd:complexType name="DerivativeCalculationMethod">
  <xsd:annotation>
    <xsd:documentation source="http://www.FpML.org" xml:lang="en">
      The method by which a derivative is computed.
    </xsd:documentation>
  </xsd:annotation>
  <xsd:simpleContent>
    <xsd:extension base="xsd:normalizedString">
      <xsd:attribute name="derivativeCalculationMethodScheme" type="xsd:anyURI" default="http://www.FpML.org" />
    </xsd:extension>
  </xsd:simpleContent>
</xsd:complexType>
```


1.3 DerivativeCalculationProcedure

1.3.1 Description:

A description of how a numerical derivative is computed.

1.3.2 Contents:


method (zero or one occurrence; of the type DerivativeCalculationMethod) The method by which a derivative is computed, e.g. analytic, numerical model, perturbation, etc.

1.3.3 Used by:

- Complex type: PricingParameterDerivative
- Complex type: SensitivitySetDefinition

1.3.4 Derived Types:

1.3.5 Figure:



1.3.6 Schema Fragment:

```
<xsd:complexType name="DerivativeCalculationProcedure">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">
      A description of how a numerical derivative is computed.
    </xsd:documentation>
  </xsd:annotation>
  <xsd:sequence>
    <xsd:element name="method" type="DerivativeCalculationMethod" minOccurs="0">
      <xsd:annotation>
        <xsd:documentation xml:lang="en">
          The method by which a derivative is computed, e.g. analytic,
          numerical model, perturbation, etc.
        </xsd:documentation>
      </xsd:annotation>
    </xsd:element>
    <xsd:group ref="DerivativeCalculationParameters.model" minOccurs="0"/>
  </xsd:sequence>
</xsd:complexType>
```

1.4 DerivativeFormula

1.4.1 Description:

A formula for computing a complex derivative from partial derivatives. Its value is the sum of the terms divided by the product of the denominator terms.

1.4.2 Contents:


term (exactly one occurrence; of the type FormulaTerm) A term of the formula. Its value is the product of the its coefficient and the referenced partial derivatives.

denominatorTerm (exactly one occurrence; of the type DenominatorTerm) A denominator term of the formula. Its value is (sum of weighted partials) ^ power.

1.4.3 Used by:

1.4.4 Derived Types:

1.4.5 Figure:



1.4.6 Schema Fragment:

```
<xsd:complexType name="DerivativeFormula">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">
      A formula for computing a complex derivative from partial
      derivatives. Its value is the sum of the terms divided by the
      product of the denominator terms.
    </xsd:documentation>
  </xsd:annotation>
  <xsd:sequence>
    <xsd:element name="term" type="FormulaTerm">
      <xsd:annotation>
        <xsd:documentation xml:lang="en">
          A term of the formula. Its value is the product of the its
          coefficient and the referenced partial derivatives.
        </xsd:documentation>
      </xsd:annotation>
    </xsd:element>
    <xsd:element name="denominatorTerm" type="DenominatorTerm">
      <xsd:annotation>
        <xsd:documentation xml:lang="en">
          A denominator term of the formula. Its value is (sum of
          weighted partials) ^ power.
        </xsd:documentation>
      </xsd:annotation>
    </xsd:element>
  </xsd:sequence>
</xsd:complexType>
```

1.5 FormulaTerm

1.5.1 Description:

A type defining a term of the formula. Its value is the product of the its coefficient and the referenced partial derivatives.

1.5.2 Contents:

coefficient (exactly one occurrence; of the type xsd:decimal) The coefficient by which this term is multiplied, typically 1 or -1.


partialDerivativeReference (one or more occurrences; of the type Reference) A reference to the partial derivative.

1.5.3 Used by:

- Complex type: DerivativeFormula

1.5.4 Derived Types:

1.5.5 Figure:



1.5.6 Schema Fragment:

```
<xsd:complexType name="FormulaTerm">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">
      A type defining a term of the formula. Its value is the product
      of the its coefficient and the referenced partial derivatives.
    </xsd:documentation>
  </xsd:annotation>
  <xsd:sequence>
    <xsd:element name="coefficient" type="xsd:decimal">
      <xsd:annotation>
        <xsd:documentation xml:lang="en">
          The coefficient by which this term is multiplied, typically 1
          or -1.
        </xsd:documentation>
      </xsd:annotation>
    </xsd:element>
    <xsd:element name="partialDerivativeReference" type="Reference" maxOccurs="unbounded">
      <xsd:annotation>
        <xsd:documentation xml:lang="en">
          A reference to the partial derivative.
        </xsd:documentation>
      </xsd:annotation>
    </xsd:element>
  </xsd:sequence>
</xsd:complexType>
```

1.6 PerturbationType

1.6.1 Description:

The type of perturbation applied to compute a derivative perturbatively.

1.6.2 Contents:


Inherited element(s): (This definition inherits the content defined by the type xsd:normalizedString)

•

1.6.3 Used by:

1.6.4 Derived Types:

1.6.5 Figure:



1.6.6 Schema Fragment:

```
<xsd:complexType name="PerturbationType">
  <xsd:annotation>
    <xsd:documentation source="http://www.FpML.org" xml:lang="en">
      The type of perturbation applied to compute a derivative
      perturbatively.
    </xsd:documentation>
  </xsd:annotation>
  <xsd:simpleContent>
    <xsd:extension base="xsd:normalizedString">
      <xsd:attribute name="perturbationTypeScheme" type="xsd:anyURI" default="http://www.fpml.org" />
    </xsd:extension>
  </xsd:simpleContent>
</xsd:complexType>
```

1.7 PricingParameterDerivative

1.7.1 Description:

A definition of the mathematical derivative with respect to a specific pricing parameter.

1.7.2 Contents:

description (zero or one occurrence; of the type xsd:string) A description, if needed, of how the derivative is computed.

Either

parameterReference (zero or one occurrence; of the type Reference) A reference to the pricing input parameter to which the sensitivity is computed. If it is omitted, the derivative definition is generic, and applies to any input point in the valuation set.

Or


inputDateReference (one or more occurrences; of the type Reference) Reference(s) to the pricing input dates that are shifted when the sensitivity is computed. Depending on the time advance method used, this list could vary. Used for describing time-advance derivatives (theta, carry, etc.)

calculationProcedure (zero or one occurrence; of the type DerivativeCalculationProcedure) The method by which a derivative is computed, e.g. analytic, numerical model, perturbation, etc., and the corresponding parameters

1.7.3 Used by:

1.7.4 Derived Types:

1.7.5 Figure:



1.7.6 Schema Fragment:

```
<xsd:complexType name="PricingParameterDerivative">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">
      A definition of the mathematical derivative with respect to a
      specific pricing parameter.
    </xsd:documentation>
  </xsd:annotation>
  <xsd:sequence>
    <xsd:element name="description" type="xsd:string" minOccurs="0">
      <xsd:annotation>
```

```

    <xsd:documentation xml:lang="en">
      A description, if needed, of how the derivative is computed.
    </xsd:documentation>
  </xsd:annotation>
</xsd:element>
<xsd:choice>
  <xsd:element name="parameterReference" type="Reference" minOccurs="0">
    <xsd:annotation>
      <xsd:documentation xml:lang="en">
        A reference to the pricing input parameter to which the
        sensitivity is computed. If it is omitted, the derivative
        definition is generic, and applies to any input point in
        the valuation set.
      </xsd:documentation>
    </xsd:annotation>
  </xsd:element>
  <xsd:element name="inputDateReference" type="Reference" maxOccurs="unbounded">
    <xsd:annotation>
      <xsd:documentation xml:lang="en">
        Reference(s) to the pricing input dates that are shifted
        when the sensitivity is computed. Depending on the time
        advance method used, this list could vary. Used for
        describing time-advance derivatives (theta, carry, etc.)
      </xsd:documentation>
    </xsd:annotation>
  </xsd:element>
</xsd:choice>
<xsd:element name="calculationProcedure" type="DerivativeCalculationProcedure" minOccurs="0">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">
      The method by which a derivative is computed, e.g. analytic,
      numerical model, perturbation, etc., and the corresponding
      parameters
    </xsd:documentation>
  </xsd:annotation>
</xsd:element>
</xsd:sequence>
<xsd:attribute name="id" type="xsd:ID"/>
</xsd:complexType>

```

1.8 PricingParameterShift

1.8.1 Description:

A definition of a shift with respect to a specific pricing parameter.

1.8.2 Contents:

parameterReference (exactly one occurrence; of the type Reference)

shift (exactly one occurrence; of the type xsd:decimal) The size of the denominator, e.g. 0.0001 = 1 bp.


shiftUnits (zero or one occurrence; of the type PriceQuoteUnits) The units of the denominator, e.g. currency. If not present, use the units of the PricingInputReference.

1.8.3 Used by:

- Complex type: DerivedValuationScenario
- Complex type: ValuationScenario

1.8.4 Derived Types:

1.8.5 Figure:



1.8.6 Schema Fragment:

```
<xsd:complexType name="PricingParameterShift">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">
      A definition of a shift with respect to a specific pricing
      parameter.
    </xsd:documentation>
  </xsd:annotation>
  <xsd:sequence>
    <xsd:element name="parameterReference" type="Reference"/>
    <xsd:element name="shift" type="xsd:decimal">
      <xsd:annotation>
        <xsd:documentation xml:lang="en">
          The size of the denominator, e.g. 0.0001 = 1 bp.
        </xsd:documentation>
      </xsd:annotation>
    </xsd:element>
    <xsd:element name="shiftUnits" type="PriceQuoteUnits" minOccurs="0">
      <xsd:annotation>
        <xsd:documentation xml:lang="en">
          The units of the denominator, e.g. currency. If not present,
          use the units of the PricingInputReference.
        </xsd:documentation>
      </xsd:annotation>
    </xsd:element>
  </xsd:sequence>
</xsd:complexType>
```

```
<xsd:attribute name="id" type="xsd:ID"/>
</xsd:complexType>
```


1.9 SensitivityDefinition

1.9.1 Description:

A set of characteristics describing a sensitivity

1.9.2 Contents:

name (zero or one occurrence; of the type xsd:string) The name of the derivative, e.g. first derivative, Hessian, etc. Typically not required, but may be used to explain more complex derivative calculations.


valuationScenarioReference (zero or one occurrence; of the type Reference) Reference to the valuation scenario to which this sensitivity definition applies. If the SensitivityDefinition occurs within a SensitivitySetDefinition, this is not required and normally not used. In this case, if it is supplied it overrides the valuationScenarioReference in the SensitivitySetDefinition.

1.9.3 Used by:

- Complex type: SensitivitySetDefinition

1.9.4 Derived Types:

1.9.5 Figure:



1.9.6 Schema Fragment:

```
<xsd:complexType name="SensitivityDefinition">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">
      A set of characteristics describing a sensitivity
    </xsd:documentation>
  </xsd:annotation>
  <xsd:sequence>
    <xsd:element name="name" type="xsd:string" minOccurs="0">
      <xsd:annotation>
        <xsd:documentation xml:lang="en">
          The name of the derivative, e.g. first derivative, Hessian,
          etc. Typically not required, but may be used to explain more
```

```

        complex derivative calculations.
    </xsd:documentation>
</xsd:annotation>
</xsd:element>
<xsd:element name="valuationScenarioReference" type="Reference" minOccurs="0">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">
            Reference to the valuation scenario to which this sensitivity
            definition applies. If the SensitivityDefinition occurs
            within a SensitivitySetDefinition, this is not required and
            normally not used. In this case, if it is supplied it
            overrides the valuationScenarioReference in the
            SensitivitySetDefinition.
        </xsd:documentation>
    </xsd:annotation>
</xsd:element>
<xsd:choice>
    <xsd:group ref="ComputedDerivative.model"/>
    <xsd:group ref="SensitivityDescription.model"/>
</xsd:choice>
</xsd:sequence>
<xsd:attribute name="id" type="xsd:ID"/>
</xsd:complexType>

```

1.10 SensitivitySetDefinition

1.10.1 Description:

A sensitivity report definition, consisting of a collection of sensitivity definitions.

1.10.2 Contents:

name (zero or one occurrence; of the type xsd:string) The name of the sensitivity set definition, e.g. "USDLIBOR curve sensitivities".

sensitivityCharacteristics (zero or one occurrence; of the type QuotationCharacteristics) The default characteristics of the quotation, e.g. type, units, etc.

valuationScenarioReference (zero or one occurrence; of the type Reference) Reference to the valuation scenario to which this sensitivity definition applies, e.g. a reference to the EOD valuation scenario. If not supplied, this sensitivity set definition is generic to a variety of valuation scenarios.

pricingInputType (zero or one occurrence; of the type PricingInputType) The type of the pricing input to which the sensitivity is shown, e.g. a yield curve or volatility matrix.

pricingInputReference (zero or one occurrence; of the type Reference) A reference to the pricing input to which the sensitivity is shown, e.g. a reference to a USDLIBOR yield curve.

scale (exactly one occurrence; of the type xsd:decimal) The size of the denominator, e.g. 0.0001 = 1 bp. For derivatives with respect to time, the default period is 1 day.

sensitivityDefinition (zero or more occurrences; of the type SensitivityDefinition) A set of sensitivity definitions. Either one per point reported, or one generic definition that applies to all points.


calculationProcedure (zero or one occurrence; of the type DerivativeCalculationProcedure) The method by which each derivative is computed, e.g. analytic, numerical model, perturbation, etc., and the corresponding parameters (eg. shift amounts).

1.10.3 Used by:

- Complex type: ValuationSet

1.10.4 Derived Types:

1.10.5 Figure:



1.10.6 Schema Fragment:

```
<xsd:complexType name="SensitivitySetDefinition">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">
      A sensitivity report definition, consisting of a collection of
      sensitivity definitions.
    </xsd:documentation>
  </xsd:annotation>
  <xsd:sequence>
    <xsd:element name="name" type="xsd:string" minOccurs="0">
      <xsd:annotation>
        <xsd:documentation xml:lang="en">
          The name of the sensitivity set definition, e.g. "USDLIBOR
          curve sensitivities".
        </xsd:documentation>
      </xsd:annotation>
    </xsd:element>
    <xsd:element name="sensitivityCharacteristics" type="QuotationCharacteristics" minOccurs="0">
      <xsd:annotation>
        <xsd:documentation xml:lang="en">
          The default characteristics of the quotation, e.g. type,
          units, etc.
        </xsd:documentation>
      </xsd:annotation>
    </xsd:element>
    <xsd:element name="valuationScenarioReference" type="Reference" minOccurs="0">
      <xsd:annotation>
        <xsd:documentation xml:lang="en">
          Reference to the valuation scenario to which this sensitivity
          definition applies, e.g. a reference to the EOD valuation
          scenario. If not supplied, this sensitivity set definition is
          generic to a variety of valuation scenarios.
        </xsd:documentation>
      </xsd:annotation>
    </xsd:element>
    <xsd:element name="pricingInputType" type="PricingInputType" minOccurs="0">
      <xsd:annotation>
        <xsd:documentation xml:lang="en">

```

```

        The type of the pricing input to which the sensitivity is
        shown, e.g. a yield curve or volatility matrix.
    </xsd:documentation>
</xsd:annotation>
</xsd:element>
<xsd:element name="pricingInputReference" type="Reference" minOccurs="0">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">
            A reference to the pricing input to which the sensitivity is
            shown, e.g. a reference to a USDLIBOR yield curve.
        </xsd:documentation>
    </xsd:annotation>
</xsd:element>
<xsd:element name="scale" type="xsd:decimal">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">
            The size of the denominator, e.g. 0.0001 = 1 bp. For
            derivatives with respect to time, the default period is 1
            day.
        </xsd:documentation>
    </xsd:annotation>
</xsd:element>
<xsd:element name="sensitivityDefinition" type="SensitivityDefinition" minOccurs="0" maxOccurs="unbounded">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">
            A set of sensitivity definitions. Either one per point
            reported, or one generic definition that applies to all
            points.
        </xsd:documentation>
    </xsd:annotation>
</xsd:element>
<xsd:element name="calculationProcedure" type="DerivativeCalculationProcedure" minOccurs="0" maxOccurs="unbounded">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">
            The method by which each derivative is computed, e.g.
            analytic, numerical model, perturbation, etc., and the
            corresponding parameters (eg. shift amounts).
        </xsd:documentation>
    </xsd:annotation>
</xsd:element>
</xsd:sequence>
<xsd:attribute name="id" type="xsd:ID"/>
</xsd:complexType>

```

1.11 WeightedPartialDerivative

1.11.1 Description:

A partial derivative multiplied by a weighting factor.

1.11.2 Contents:

partialDerivativeReference (exactly one occurrence; of the type Reference) A reference to a partial derivative defined in the ComputedDerivative.model, i.e. defined as part of this sensitivity definition.


weight (exactly one occurrence; of the type xsd:decimal) The weight factor to be applied to the partial derivative, e.g. 1 or -1, or some other scaling value.

1.11.3 Used by:

- Complex type: DenominatorTerm

1.11.4 Derived Types:

1.11.5 Figure:



1.11.6 Schema Fragment:

```
<xsd:complexType name="WeightedPartialDerivative">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">
      A partial derivative multiplied by a weighting factor.
    </xsd:documentation>
  </xsd:annotation>
  <xsd:sequence>
    <xsd:element name="partialDerivativeReference" type="Reference">
      <xsd:annotation>
        <xsd:documentation xml:lang="en">
          A reference to a partial derivative defined in the
          ComputedDerivative.model, i.e. defined as part of this
          sensitivity definition.
        </xsd:documentation>
      </xsd:annotation>
    </xsd:element>
    <xsd:element name="weight" type="xsd:decimal">
      <xsd:annotation>
        <xsd:documentation xml:lang="en">
          The weight factor to be applied to the partial derivative,
          e.g. 1 or -1, or some other scaling value.
        </xsd:documentation>
      </xsd:annotation>
    </xsd:element>
  </xsd:sequence>
</xsd:complexType>
```

2 Schema listing

```
<xsd:schema targetNamespace="http://www.fpml.org/2005/FpML-4-2" elementFormDefault="qualified"
  <xsd:include schemaLocation="fpml-mktenv-4-2.xsd"/>
  <xsd:complexType name="DenominatorTerm">
    <xsd:annotation>
      <xsd:documentation xml:lang="en">
        The type defining a denominator term of the formula. Its value
        is (sum of weighted partials) ^ power.
      </xsd:documentation>
    </xsd:annotation>
    <xsd:sequence>
      <xsd:element name="weightedPartial" type="WeightedPartialDerivative">
        <xsd:annotation>
          <xsd:documentation xml:lang="en">
            A partial derivative multiplied by a weighting factor.
          </xsd:documentation>
        </xsd:annotation>
      </xsd:element>
      <xsd:element name="power" type="xsd:integer">
        <xsd:annotation>
          <xsd:documentation xml:lang="en">
            The power to which this term is raised.
          </xsd:documentation>
        </xsd:annotation>
      </xsd:element>
    </xsd:sequence>
  </xsd:complexType>
  <xsd:complexType name="DerivativeCalculationMethod">
    <xsd:annotation>
      <xsd:documentation source="http://www.FpML.org" xml:lang="en">
        The method by which a derivative is computed.
      </xsd:documentation>
    </xsd:annotation>
    <xsd:simpleContent>
      <xsd:extension base="xsd:normalizedString">
        <xsd:attribute name="derivativeCalculationMethodScheme" type="xsd:anyURI" default="http
      </xsd:extension>
    </xsd:simpleContent>
  </xsd:complexType>
  <xsd:complexType name="DerivativeCalculationProcedure">
    <xsd:annotation>
      <xsd:documentation xml:lang="en">
        A description of how a numerical derivative is computed.
      </xsd:documentation>
    </xsd:annotation>
    <xsd:sequence>
      <xsd:element name="method" type="DerivativeCalculationMethod" minOccurs="0">
        <xsd:annotation>
          <xsd:documentation xml:lang="en">
            The method by which a derivative is computed, e.g.
            analytic, numerical model, perturbation, etc.
          </xsd:documentation>
        </xsd:annotation>
      </xsd:element>
      <xsd:group ref="DerivativeCalculationParameters.model" minOccurs="0"/>
    </xsd:sequence>
  </xsd:complexType>
  <xsd:complexType name="DerivativeFormula">
    <xsd:annotation>
      <xsd:documentation xml:lang="en">
        A formula for computing a complex derivative from partial
        derivatives. Its value is the sum of the terms divided by the
        product of the denominator terms.
      </xsd:documentation>
    </xsd:annotation>
    <xsd:sequence>
      <xsd:element name="term" type="FormulaTerm">
        <xsd:annotation>
          <xsd:documentation xml:lang="en">
            A term of the formula. Its value is the product of the its
            coefficient and the referenced partial derivatives.
          </xsd:documentation>
        </xsd:annotation>
      </xsd:element>
      <xsd:element name="denominatorTerm" type="DenominatorTerm">
        <xsd:annotation>
          <xsd:documentation xml:lang="en">
            A denominator term of the formula. Its value is (sum of
            weighted partials) ^ power.
          </xsd:documentation>
        </xsd:annotation>
      </xsd:element>
    </xsd:sequence>
  </xsd:complexType>
```

```

        </xsd:annotation>
    </xsd:element>
</xsd:sequence>
</xsd:complexType>
<xsd:complexType name="FormulaTerm">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">
            A type defining a term of the formula. Its value is the product
            of the its coefficient and the referenced partial derivatives.
        </xsd:documentation>
    </xsd:annotation>
    <xsd:sequence>
        <xsd:element name="coefficient" type="xsd:decimal">
            <xsd:annotation>
                <xsd:documentation xml:lang="en">
                    The coefficient by which this term is multiplied, typically
                    1 or -1.
                </xsd:documentation>
            </xsd:annotation>
        </xsd:element>
        <xsd:element name="partialDerivativeReference" type="Reference" maxOccurs="unbounded">
            <xsd:annotation>
                <xsd:documentation xml:lang="en">
                    A reference to the partial derivative.
                </xsd:documentation>
            </xsd:annotation>
        </xsd:element>
    </xsd:sequence>
</xsd:complexType>
<xsd:complexType name="PerturbationType">
    <xsd:annotation>
        <xsd:documentation source="http://www.FpML.org" xml:lang="en">
            The type of perturbation applied to compute a derivative
            perturbatively.
        </xsd:documentation>
    </xsd:annotation>
    <xsd:simpleContent>
        <xsd:extension base="xsd:normalizedString">
            <xsd:attribute name="perturbationTypeScheme" type="xsd:anyURI" default="http://www.fpm1
            </xsd:extension>
        </xsd:simpleContent>
    </xsd:complexType>
<xsd:complexType name="PricingParameterDerivative">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">
            A definition of the mathematical derivative with respect to a
            specific pricing parameter.
        </xsd:documentation>
    </xsd:annotation>
    <xsd:sequence>
        <xsd:element name="description" type="xsd:string" minOccurs="0">
            <xsd:annotation>
                <xsd:documentation xml:lang="en">
                    A description, if needed, of how the derivative is
                    computed.
                </xsd:documentation>
            </xsd:annotation>
        </xsd:element>
        <xsd:choice>
            <xsd:element name="parameterReference" type="Reference" minOccurs="0">
                <xsd:annotation>
                    <xsd:documentation xml:lang="en">
                        A reference to the pricing input parameter to which the
                        sensitivity is computed. If it is omitted, the derivative
                        definition is generic, and applies to any input point in
                        the valuation set.
                    </xsd:documentation>
                </xsd:annotation>
            </xsd:element>
            <xsd:element name="inputDateReference" type="Reference" maxOccurs="unbounded">
                <xsd:annotation>
                    <xsd:documentation xml:lang="en">
                        Reference(s) to the pricing input dates that are shifted
                        when the sensitivity is computed. Depending on the time
                        advance method used, this list could vary. Used for
                        describing time-advance derivatives (theta, carry, etc.)
                    </xsd:documentation>
                </xsd:annotation>
            </xsd:element>
        </xsd:choice>
        <xsd:element name="calculationProcedure" type="DerivativeCalculationProcedure" minOccurs=
        <xsd:annotation>
            <xsd:documentation xml:lang="en">

```



```

        The method by which a derivative is computed, e.g.
        analytic, numerical model, perturbation, etc., and the
        corresponding parameters
    </xsd:documentation>
</xsd:annotation>
</xsd:element>
</xsd:sequence>
<xsd:attribute name="id" type="xsd:ID"/>
</xsd:complexType>
<xsd:complexType name="PricingParameterShift">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">
            A definition of a shift with respect to a specific pricing
            parameter.
        </xsd:documentation>
    </xsd:annotation>
    <xsd:sequence>
        <xsd:element name="parameterReference" type="Reference"/>
        <xsd:element name="shift" type="xsd:decimal">
            <xsd:annotation>
                <xsd:documentation xml:lang="en">
                    The size of the denominator, e.g. 0.0001 = 1 bp.
                </xsd:documentation>
            </xsd:annotation>
        </xsd:element>
        <xsd:element name="shiftUnits" type="PriceQuoteUnits" minOccurs="0">
            <xsd:annotation>
                <xsd:documentation xml:lang="en">
                    The units of the denominator, e.g. currency. If not
                    present, use the units of the PricingInputReference.
                </xsd:documentation>
            </xsd:annotation>
        </xsd:element>
    </xsd:sequence>
    <xsd:attribute name="id" type="xsd:ID"/>
</xsd:complexType>
<xsd:complexType name="SensitivityDefinition">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">
            A set of characteristics describing a sensitivity
        </xsd:documentation>
    </xsd:annotation>
    <xsd:sequence>
        <xsd:element name="name" type="xsd:string" minOccurs="0">
            <xsd:annotation>
                <xsd:documentation xml:lang="en">
                    The name of the derivative, e.g. first derivative, Hessian,
                    etc. Typically not required, but may be used to explain
                    more complex derivative calculations.
                </xsd:documentation>
            </xsd:annotation>
        </xsd:element>
        <xsd:element name="valuationScenarioReference" type="Reference" minOccurs="0">
            <xsd:annotation>
                <xsd:documentation xml:lang="en">
                    Reference to the valuation scenario to which this
                    sensitivity definition applies. If the
                    SensitivityDefinition occurs within a
                    SensitivitySetDefinition, this is not required and normally
                    not used. In this case, if it is supplied it overrides the
                    valuationScenarioReference in the SensitivitySetDefinition.
                </xsd:documentation>
            </xsd:annotation>
        </xsd:element>
        <xsd:choice>
            <xsd:group ref="ComputedDerivative.model"/>
            <xsd:group ref="SensitivityDescription.model"/>
        </xsd:choice>
    </xsd:sequence>
    <xsd:attribute name="id" type="xsd:ID"/>
</xsd:complexType>
<xsd:complexType name="SensitivitySetDefinition">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">
            A sensitivity report definition, consisting of a collection of
            sensitivity definitions.
        </xsd:documentation>
    </xsd:annotation>
    <xsd:sequence>
        <xsd:element name="name" type="xsd:string" minOccurs="0">
            <xsd:annotation>
                <xsd:documentation xml:lang="en">
                    The name of the sensitivity set definition, e.g. "USDLIBOR

```

```

        curve sensitivities".
    </xsd:documentation>
</xsd:annotation>
</xsd:element>
<xsd:element name="sensitivityCharacteristics" type="QuotationCharacteristics" minOccurs="1" maxOccurs="1">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">
            The default characteristics of the quotation, e.g. type,
            units, etc.
        </xsd:documentation>
    </xsd:annotation>
</xsd:element>
<xsd:element name="valuationScenarioReference" type="Reference" minOccurs="0" maxOccurs="1">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">
            Reference to the valuation scenario to which this
            sensitivity definition applies, e.g. a reference to the EOD
            valuation scenario. If not supplied, this sensitivity set
            definition is generic to a variety of valuation scenarios.
        </xsd:documentation>
    </xsd:annotation>
</xsd:element>
<xsd:element name="pricingInputType" type="PricingInputType" minOccurs="0" maxOccurs="1">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">
            The type of the pricing input to which the sensitivity is
            shown, e.g. a yield curve or volatility matrix.
        </xsd:documentation>
    </xsd:annotation>
</xsd:element>
<xsd:element name="pricingInputReference" type="Reference" minOccurs="0" maxOccurs="1">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">
            A reference to the pricing input to which the sensitivity
            is shown, e.g. a reference to a USDLIBOR yield curve.
        </xsd:documentation>
    </xsd:annotation>
</xsd:element>
<xsd:element name="scale" type="xsd:decimal">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">
            The size of the denominator, e.g. 0.0001 = 1 bp. For
            derivatives with respect to time, the default period is 1
            day.
        </xsd:documentation>
    </xsd:annotation>
</xsd:element>
<xsd:element name="sensitivityDefinition" type="SensitivityDefinition" minOccurs="0" maxOccurs="1">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">
            A set of sensitivity definitions. Either one per point
            reported, or one generic definition that applies to all
            points.
        </xsd:documentation>
    </xsd:annotation>
</xsd:element>
<xsd:element name="calculationProcedure" type="DerivativeCalculationProcedure" minOccurs="0" maxOccurs="1">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">
            The method by which each derivative is computed, e.g.
            analytic, numerical model, perturbation, etc., and the
            corresponding parameters (eg. shift amounts).
        </xsd:documentation>
    </xsd:annotation>
</xsd:element>
</xsd:sequence>
<xsd:attribute name="id" type="xsd:ID"/>
</xsd:complexType>
<xsd:complexType name="WeightedPartialDerivative">
    <xsd:annotation>
        <xsd:documentation xml:lang="en">
            A partial derivative multiplied by a weighting factor.
        </xsd:documentation>
    </xsd:annotation>
</xsd:complexType>
<xsd:sequence>
    <xsd:element name="partialDerivativeReference" type="Reference">
        <xsd:annotation>
            <xsd:documentation xml:lang="en">
                A reference to a partial derivative defined in the
                ComputedDerivative.model, i.e. defined as part of this
                sensitivity definition.
            </xsd:documentation>
        </xsd:annotation>
    </xsd:element>

```

```

</xsd:element>
<xsd:element name="weight" type="xsd:decimal">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">
      The weight factor to be applied to the partial derivative,
      e.g. 1 or -1, or some other scaling value.
    </xsd:documentation>
  </xsd:annotation>
</xsd:element>
</xsd:sequence>
</xsd:complexType>
<xsd:group name="AnalyticDerivativeParameters.model">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">
      Parameters used in the computation of a derivative using
      analytical (closed form formula) techniques.
    </xsd:documentation>
  </xsd:annotation>
  <xsd:sequence>
    <xsd:element name="derivativeFormula" type="xsd:string" minOccurs="0">
      <xsd:annotation>
        <xsd:documentation xml:lang="en">
          The formula used to compute the derivative (perhaps could
          be updated to use the Formula type in EQS.).
        </xsd:documentation>
      </xsd:annotation>
    </xsd:element>
  </xsd:sequence>
</xsd:group>
<xsd:group name="ComputedDerivative.model">
  <xsd:annotation>
    <xsd:documentation source="http://www.FpML.org" xml:lang="en">
      A group describing a derivative as combination of partial
      derivatives.
    </xsd:documentation>
  </xsd:annotation>
  <xsd:sequence>
    <xsd:element name="partialDerivative" type="PricingParameterDerivative" maxOccurs="unbound">
      <xsd:annotation>
        <xsd:documentation xml:lang="en">
          A partial derivative of the measure with respect to an
          input.
        </xsd:documentation>
      </xsd:annotation>
    </xsd:element>
    <xsd:element name="formula" type="DerivativeFormula" minOccurs="0">
      <xsd:annotation>
        <xsd:documentation xml:lang="en">
          A formula defining how to compute the derivative from the
          partial derivatives. If absent, the derivative is just the
          product of the partial derivatives. Normally only required
          for more higher-order derivatives, e.g. Hessians.
        </xsd:documentation>
      </xsd:annotation>
    </xsd:element>
  </xsd:sequence>
</xsd:group>
<xsd:group name="DerivativeCalculationParameters.model">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">
      Parameters used in the computation of a derivative.
    </xsd:documentation>
  </xsd:annotation>
  <xsd:choice>
    <xsd:group ref="FiniteDifferenceDerivativeParameters.model"/>
    <xsd:group ref="AnalyticDerivativeParameters.model"/>
    <xsd:group ref="SubstitutionDerivativeParameters.model"/>
  </xsd:choice>
</xsd:group>
<xsd:group name="FiniteDifferenceDerivativeParameters.model">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">
      Parameters used in the computation of a derivative using
      numerical (finite difference) techniques.
    </xsd:documentation>
  </xsd:annotation>
  <xsd:sequence>
    <xsd:element name="perturbationAmount" type="xsd:decimal" minOccurs="0">
      <xsd:annotation>
        <xsd:documentation xml:lang="en">
          The size and direction of the perturbation used to compute
          the derivative, e.g. 0.0001 = 1 bp.
        </xsd:documentation>
      </xsd:annotation>
    </xsd:element>
  </xsd:sequence>
</xsd:group>

```

```

    </xsd:annotation>
  </xsd:element>
  <xsd:element name="averaged" type="xsd:boolean">
    <xsd:annotation>
      <xsd:documentation xml:lang="en">
        The value is calculated by perturbing by the
        perturbationAmount and then the negative of the
        perturbationAmount and then averaging the two values (i.e.
        the value is half of the difference between perturbing up
        and perturbing down).
      </xsd:documentation>
    </xsd:annotation>
  </xsd:element>
  <xsd:element name="perturbationType" type="PerturbationType" minOccurs="0">
    <xsd:annotation>
      <xsd:documentation xml:lang="en">
        The type of perturbation, if any, used to compute the
        derivative (Absolute vs Relative).
      </xsd:documentation>
    </xsd:annotation>
  </xsd:element>
</xsd:sequence>
</xsd:group>
<xsd:group name="SensitivityDescription.model">
  <xsd:annotation>
    <xsd:documentation source="http://www.FpML.org" xml:lang="en">
      A group describing a specific sensitivity without an explicit
      reference to the market data input point.
    </xsd:documentation>
  </xsd:annotation>
  <xsd:choice>
    <xsd:element name="term" type="TimeDimension">
      <xsd:annotation>
        <xsd:documentation xml:lang="en">
          The time dimension of the sensitivity point (tenor and/or
          date)
        </xsd:documentation>
      </xsd:annotation>
    </xsd:element>
    <xsd:group ref="PricingCoordinateOrReference.model" maxOccurs="unbounded">
      <xsd:annotation>
        <xsd:documentation xml:lang="en">
          The input coordinates, or references to them (e.g.
          expiration, strike, tenor).
        </xsd:documentation>
      </xsd:annotation>
    </xsd:group>
  </xsd:choice>
</xsd:group>
<xsd:group name="SubstitutionDerivativeParameters.model">
  <xsd:annotation>
    <xsd:documentation xml:lang="en">
      Parameters used in the computation of a derivative by
      substituting a supplied market environment.
    </xsd:documentation>
  </xsd:annotation>
  <xsd:sequence>
    <xsd:element name="replacementMarketInput" type="Reference">
      <xsd:annotation>
        <xsd:documentation xml:lang="en">
          A reference to the replacement version of the market input,
          e.g. a bumped yield curve.
        </xsd:documentation>
      </xsd:annotation>
    </xsd:element>
  </xsd:sequence>
</xsd:group>
</xsd:schema>

```