


Structure of a typical FpML message:





FpML root element. There are many root elements defined in FpML for the different message types and business processes. (see *Business Processes* below for full list)

The **header** contains standard envelope information used for electronic messaging. Envelope fields vary depending on the base message type

Additional fields for **message correlation** i.e., linking successive messages together (response, correction, retraction)

The **payload** of the message is determined by choosing one business event (e.g., trade, increase, termination) (the set of available events may vary from message to message)

A **product** can be specified as part of the event. Products are defined for the different asset classes (e.g., IRD, CD, FX) (see *Products Framework* for full list) Product representation can be looser or tighter depending on the view (e.g., Confirmation, Reporting)



Business Processes (continued)						
	P	C	R	RK	T	L
messageRejected	Y	Y	Y	Y	Y	N
requestRetransmission	Y	Y	Y	Y	N	N
requestEventStatus	Y	Y	Y	Y	Y	N
eventStatusResponse	Y	Y	Y	Y	Y	N
eventStatusException	Y	Y	Y	Y	Y	N
serviceNotification	Y	Y	Y	Y	Y	N
serviceNotificationException	Y	Y	Y	Y	Y	N
valuationReport	N	N	Y	Y	N	N
valuationReportAcknowledgement	N	N	Y	Y	N	N
valuationReportException	N	N	Y	Y	N	N
valuationReportRetracted	N	N	Y	Y	N	N
verificationStatusNotification	Y	Y	Y	Y	Y	N
verificationStatusAcknowledgement	Y	Y	Y	Y	Y	N
verificationStatusException	Y	Y	Y	Y	Y	N

Anatomy of an FpML Message (e.g., requestExecution)

